


ROMET

Rotary Gas Meters



HARD METRIC G650 200 mm (8") FLANGE CONNECTION

TECHNICAL SPECIFICATION


Connection (Flange)	DN/PN16 ANSI 125FF	200 mm 8"
MAOP	(bar)	12
Flow Capacity	(m³/h)	1000
Rangeability* (up to 1:160 @ atmospheric condition, according to EN12480 & OIML R137/1 requirement)		1:160
Start Rate	(m³/h)	.623
Stop Rate	(m³/h)	.396
Differential @ 100% Flow	(mbar)	8.22
Instrument Drive Rate	(m³/rev)	1.0/10.0
LF Pulser (Optional)	(m³/pulse)	1.0/10.0

^{*}Note: It should be noted, that moving parts in the meters with a greater rangeability ratio are made to high class accuracy and tight tolerances.

Improper installation, stresses on piping system due to temperature changes, settling and gas conditions can create a risk of meter rejection.

CORRECTED FLOW CAPACITY AND TYPICAL ACCURACY GUIDE

G650 METER (SM³/H)		
Gauge Pressure Bar 0.012	G650 Qmax = 1000 m³/ hr	
0.05	1049.3	
0.1	1098.7	
0.5	1493.5	
1.0	1986.9	
1.5	2480.4	
2.0	2973.8	
2.5	3467.3	
3.0	3960.8	
5.0	5934.6	
7.5	8401.9	
10.0	10869.2	
11.0	11856.1	
12.0	12843.1	





ROMET

GAS METERS AND ELECTRONIC INSTRUMENTS

Phone 905-624-1591 USA 1-800-387-3201 www.rometlimited.com • email: romet@rometlimited.com

The values quoted are typical of normal production. They do not constitute a specification. Romet Limited reserves the right to change any information in this literature without notice. All of the information and data in this literature has been carefully compiled and thoroughly checked. However, Romet Limited will not assume responsibility for any possible omissions or errors.

ROMET and ROMET & DESIGN are registered trademarks of Romet Limited. Romet Limited's gas metering technology is protected under U.S.Patent No.4,910,519 and 6,453,721 and Canadian Patent No.1,293,568.